



**ATTACHMENT
TO
APPENDIX I TO MANAGEMENT SYSTEM CERTIFICATE**

**マネジメントシステム認証証明書
アペンディックス I に対する付属書**

USE OF CERTIFICATION MARKS

認証マークの使用

1. INTRODUCTION

This procedure describes the conditions under which certificate holders of DNV Business Assurance Japan KK with a valid management system certification may use the associated marks. (customer wish to use the DNV mark on its own, reference is made to paragraph 4 hereafter.)

2. CERTIFICATION MARK

2.1 Certification holders of a certificate issued by DNV Business Assurance Japan KK under its management system certification scheme are entitled to use the certification mark combinations to announce / demonstrate the fact of certification publicly. (See sample, separately)

2.2 Contents of the logo mark may be revised.
Latest version of this procedure and logo marks are put on the website of DNV Business Assurance Japan KK as needed.

3. CONDITIONS OF USE (General)

3.1 Certificate holders may use only the marks relevant to the applied standard to which they have been certified.

3.2 Certificate holders are entitled to use the certification marks as sample illustrated separately within only their certification scope on descriptions, promotional material, envelopes, letterhead, invoices and so on.

Using the mark on name cards is limited to those personnel who are engaged in activities within the certified scope.

It is not allowed to use the certification mark, for example, for the business card which indicates the information about outside of the scope (product, activity, business site and sales site etc.) on either sides, and the Website display which indicates the information about outside of the scope (product, activity, business site and sales site etc.) on the same page as well.

However, it may be applied provided there is supplemental explanation that clearly describes for the scope of the certification acquired.

It shall be an expression that doesn't receive misunderstanding from any third party, for example, "ISO9001 is certified to xx Factory only", "ISO9001 is certified to the Scope of "Design and Manufacture of Product xx" only", etc.

1. 序文

この手順書は DNV ビジネス・アシュアランス・ジャパン株式会社よりマネジメントシステム認証を保持する顧客に対して、認証マークの使用条件を述べたものである。(DNV 単体マークを使用希望の場合は後述の 4 項を参照のこと)

2. 認証マーク

2.1 マネジメントシステム認証スキームに基づいて DNV ビジネス・アシュアランス・ジャパン株式会社の認証を受けた企業は、その認証を受けた事実を社外に公表するために認証マークを使用することが出来る。(別途、サンプル参照)

2.2 認証マーク内の記載内容及び使用条件は変更される場合がある。本手順書及び認証マーク最新版は、随時、DNV ビジネス・アシュアランス・ジャパン株式会社のウェブサイト上に掲載される。

3. 使用条件 (一般)

3.1 認証証明書を取得した企業は、認証に該当する規格のマークのみ使用することが出来る。

3.2 認証証明書を取得した企業は、認証マーク (別途サンプル参照) を、認証範囲内においてのみ、説明書、宣伝用資料、封筒、レターヘッド、請求書等に使用することが出来る。

尚、名刺に使用する場合は、認証を受けた対象範囲の業務に従事する者のみが使用できるものとする。

従って、例えば、表面あるいは裏面に認証範囲外の情報 (製品、活動、事業所、営業所など) を記載した名刺は使用できない。同じく、認証範囲外の情報 (製品、活動、事業所、営業所など) を記載したウェブサイト画面頁等には、認証マークを使用できない。

但し、取得した認証範囲を明確に規定した補足説明がある場合はこの限りではない。

例えば、「ISO9001 は xx 工場のみ認証取得」、
「ISO9001 は認証範囲 (製品 xx の設計・製造) に限り認証取得」等々、第三者から見て、誤解を受けない表現である事を前提とする。



The data format to be used are Vector Data (EPS) for printing and Raster Data (JPEG) for website respectively.

3.3 Colour and size of certification mark may be reproduced according to the rules of accreditation scheme for applicable certification mark indicated hereafter.

However, it must always be reproduced in its entirety, any proportions or contents of provided sample shall not be changed, and surely including the surrounding outline. Certification mark must have clear contrast to the background colour.

Use of the mark of any accreditation body alone is strictly prohibited.

3.3.1 JAB Certification Mark

ISO17021 type JAB certification mark has been introduced from September 15th, 2008. The certificate holder who is certified after September 15th 2008 shall use new one (as per 3.3.1.1) if they use the certification mark.

Present JAB certification mark has been introduced from November, 2005. The certificate holder who is certified after November, 2005 shall use present one (as per 3.3.1.2) if they use the certification mark. This present JAB certification mark will be expiry on May 21st, 2011

Transition period to replace former type (as per 3.3.1.3) with present type is sanctioned for the certificate holder who has already been certified before November, 2005, then the certificate holder (if they use the certification mark) shall have implemented the present type not later than September 15th, 2008.

Regarding present type of JAB certification mark which was introduced from November, 2005 and ISO17021 type of JAB certification mark which was introduced from September 15th, 2008, following procedure must be complied from the safeguarding the trade mark point of view.

- The certificate holder can have the title to use the certification mark after agreement to follow the rule to safeguard the symbol and to prevent its leakage. (by means of application and agreement form)
- The certificate holder is prohibited to reduce its resolution by processing or changing the saving form etc.
- The certificate holder shall prepare the list for subcontractor who is adopted to print or make the website with the certification mark, after agreement by the subcontractor to safeguard the symbol and to prevent its leakage.

3.3.1.1 JAB Certificate Mark (ISO17021 type)

JAB certification mark can be reproduced in any size. Even the size being reduced, all letters within the mark shall be clearly legible.

使用できるデータ形式は、印刷物用は印刷用データ (EPS)、ウェブサイト掲載用は画面用データ (JPEG) とする。

3.3 認証マークの色及びサイズは、下記の該当する認定スキームによる認証マークの条件を守って複製されなければならない。

拡大、縮小する際は、DNV から提供されたサンプルの縦横比、あるいはその内容を一切変えてはならず、必ず外枠の線を含めてその全体を複製しなければならない。

認証マークは地色との明瞭な対比をもたせて表示しなければならない。

尚、各認定機関のマークを単体使用することは固く禁じられている。

3.3.1 JAB 認証マーク

2008年9月15日より、ISO17021 対応 JAB 認証マークが導入された。2008年9月15日以降に認証取得した企業が JAB 認証マークを使用する場合には、本マーク (下記の 3.3.1.1 項) を使用すること。

2005年11月より現 JAB 認証マークが導入された。2005年11月以降に認証取得した企業が JAB 認証マークを使用する場合には、現マーク (下記の 3.3.1.2 項) を使用すること。又、現マークは 2011年5月22日以降無効となる。

2005年11月以前に既に認証を取得している企業が現 JAB 認証マークを使用する場合は、旧マーク (下記の 3.3.1.3 項) から現マークへの移行期間が設けられているが、旧マークは 2008年9月16日以降無効となる。

尚、2005年11月より導入された現タイプ及び 2008年9月15日より導入された ISO17021 対応 JAB 認証マークに関しては、登録商標保護のための下記管理手順を遵守しなければならない。

- ・ 認証取得した企業は、認定シンボル保護及び漏洩防止のための管理を行なうことについての同意を表明した上で、認証マークを使用することが出来る。(申請書兼同意書による)
- ・ 認証取得した企業は、上記データに対して、解像度を低めるような加工、保存形式の変更等は一切してはならない。
- ・ 認証取得した企業が外部に印刷あるいはウェブサイト作成依頼等を行なう場合には、その業者による認定シンボル保護及び漏洩防止のための同意を得るとともに、その業者の一覧表を備えなければならない。

3.3.1.1 JAB 認証マーク (ISO17021 タイプ)

JAB 認証マークのサイズはどのようなサイズに複製しても良い。縮小する場合、マーク内の文字は明瞭に表示できなければならない。



The basic colour of JAB accreditation mark is blue (Mansell 2.5PB 3.5/10, Dai-Nippon Ink DIC 579, Pantone 300C or equivalent). Black, gray, gold or silver colour may also be used. Internal patterns (such as \wedge and \equiv part) are in the plain and clear contrast with its background.

The surrounding outline of the mark and all letters within the mark shall be black.

However, the whole mark (including outline and letters) may be indicated in a single colour only in case of use on the printed paper with the same single colour as a predominant ink colour of the document.

JAB 認定マークの基本色は、青色（マンセル 2.5PB 3.5/10, 大日本インキ KK DIC 579, PANTONE 300C 又はその近似色）とする。サブカラーとして、黒、灰、金、銀色の表示を認める。また、内部の柄（ \wedge 部及び \equiv 部）は背景との対比が明瞭な無地とし、マークの外枠及びマーク内の全ての文字は黒とする。

但し、単色刷りの印刷物に使用する場合は、マーク全体（枠及び文字を含む）を、その印刷で使用されている色と同じ単色で表示しても良い。



3.3.1.2 JAB Certification Mark (former type)

After May 22nd, 2011, No Customers can use this Certification Mark.

3.3.1.2 JAB 認証マーク（旧タイプ）

2011年5月22日以降、如何なる企業も本マークを使用する事は出来ない。



3.3.1.3 JAB Certification Mark (former type)

After September 16th, 2008, No Customers can use this Certification Mark.

3.3.1.3 JAB 認証マーク（旧タイプ）

2008年9月16日以降、如何なる企業も本マークを使用する事は出来ない。



3.3.2 RvA Certification Mark

ISO17021 type RvA certification mark has been introduced from September 15th, 2008 which is same for ISO9001 and ISO14001. The certificate holder who is certified after September 15th 2008 shall use new one (as per 3.3.2.1) if they use the certification mark.

Present type RvA certification mark has been introduced from June, 2003. The certificate holder who is certified after June, 2003 shall use present one (as per 3.3.2.2) if they use the certification mark. This present RvA certification mark for ISO14001 will be expiry on September 15th, 2011.

Transition period to replace former type (as per 3.3.2.3) with new type is sanctioned for the certificate holder who has already been certified before June, 2003, then the certificate holder (if they use the certification mark) shall have implemented the new type not later than June 1st, 2007.

3.3.2 RvA 認証マーク

2008年9月15日より、ISO17021 対応 RvA 認証マークが導入され、ISO9001、ISO14001 共に同一のマークとなった。2008年9月15日以降に認証取得した企業が RvA 認証マークを使用する場合には、本マーク（下記の 3.3.2.1 項）を使用すること。

2003年6月より、現タイプの RvA 認証マークが導入された。2003年6月以降に認証取得した企業が RvA 認証マークを使用する場合には、現マーク（下記の 3.3.2.2 項）を使用すること。又、ISO14001 用の現マークは 2011年9月16日以降無効となる。

2003年6月以前に既に認証を取得している企業が RvA 認証マークを使用する場合は、旧マーク（下記の 3.3.2.3 項）から新マークへの移行期間が設けられているが、遅くとも 2007年6月1日以降には、新しい認証マークを使用していなければならない。



3.3.2.1 RvA Certification Mark (ISO17021 type)

RvA certification mark can be reproduced in any size, however the size of the RvA logo (including the two lines of text) shall not exceed 34x28 mm (width x height). The certification mark shall not be larger than the certificate holders own logo on the same letter head etc. The certification mark may be used in black, the one (company style) colour with which a letterhead is printed, or in the exact original colours as indicated hereafter.

The colour of the new RvA mark is:

Orange : PMS 131 (DIC 567) or

Blue : PMS 296 (DIC 434)

3.3.2.1 RvA 認証マーク (ISO17021 タイプ)

RvA 認証マークのサイズはどのようなサイズに複製しても良いが、RvA ロゴは、その文字部分（2行）を含めて最大幅 34mm×高さ 28mm を超えてはならない。認証マークは同じレターヘッド等に使われているその企業のロゴより大きくしてはならない。認証マークの色は黒、レターヘッドの印刷と同じ色、もしくは下記の指定色を使用しなければならない。

RvA マーク（新）の色は：黄土色：PMS 131 (DIC 567) 又はブルー：PMS 296 (DIC 434)



ISO9001, 14001 共通

3.3.2.2 RvA Certification Mark (former type)

After September 16th, 2011, No Customers can use this Certification Mark for ISO14001.

3.3.2.2 RvA 認証マーク (旧タイプ)

2011年9月16日以降、如何なる企業もISO14001用の本マークを使用する事は出来ない。



ISO9001 用



ISO14001 用

3.3.2.3 RvA Certification Mark (former type)

After June 1st, 2007, No Customers can use this Certification Mark

3.3.2.3 RvA 認証マーク (旧タイプ)

2007年6月1日以降、如何なる企業も本マークを使用する事は出来ない。



3.3.3 UKAS Certification Mark

ISO17021 type UKAS certification mark has been introduced from October 18th, 2010 which is same for ISO9001, ISO14001 and Information Security. The certificate holder who is certified after October 18th, 2010 shall use new one (as per 3.3.3.1) if they use the certification mark.

Transition period to replace former type (as per 3.3.3.2) with new type is sanctioned for the certificate holder who has already been certified before October 18th, 2010, then the certificate holder (if they use the certification mark) shall have implemented the new type not later than September 1st, 2014.

3.3.3 UKAS 認証マーク

2010年10月18日より、ISO17021 対応 UKAS 認証マークが導入され、ISO9001、ISO14001、情報セキュリティ、全てが同一のマークとなった。2010年10月18日以降に認証取得した企業が UKAS 認証マークを使用する場合には、新マーク（下記の 3.3.3.1 項）を使用すること。

2010年10月18日以前に既に認証を取得している企業が UKAS 認証マークを使用する場合は、旧マーク（下記の 3.3.3.2 項）から新マークへの移行期間が設けられているが、遅くとも 2014年9月1日以降には、新しい認証マークを使用していなければならない。



3.3.3.1 UKAS Certification Mark (ISO17021 type)

UKAS certification mark can be reproduced in any size, however the size of UKAS logo shall have a minimum height of 20 mm, and shall not be greater than 30 mm in height when used on A4 paper. And it shall be fully legible in reproducing.

The certification mark may be used in black, the one (company style) colour with which a letterhead is printed, or in the exact original colours as indicated hereafter.

The colour of the UKAS mark is:

Gold : PMS 872

Blue : PMS Reflex Blue

Red : PMS Warm Red

Green : PMS 347

In addition to above 3.2, following restriction are to be referred for UKAS certification marks, as this may indicate/mislead the product item is certified.

- closing of any nature, mugs, plates, utensils, pens, pencils, clocks, automobiles, vehicle stickers, flags, signboards, window stickers, etc.

The TickIT mark must be printed either one colour or in the colours prescribed by DISK TickIT Office. There are; Black for circles and words inside circles; Red (Pantone 032) for the foreground Tick; and Warm Grey (Pantone 8 or 30% black) used for the background Tick and letter "IT".

3.3.3.2 UKAS Certification Mark (former type)

After September 1st, 2014, No Customers can use this Certification Mark.

3.3.4 JIPDEC Certification Mark (Basic Condition)

New type JIPDEC certification mark has been introduced from October 1st, 2011.

The certificate holder who is certified after October 1st, 2011 shall use new one (as per 3.3.4.1) if they use the certification mark.

3.3.3.1 UKAS 認証マーク (ISO17021 タイプ)

UKAS 認証マークのサイズはどのようなサイズに複製しても良いが、A4 紙に使用する場合、UKAS ロゴの高さは 20mm 以上 30mm 以下でなければならない。縮小する際には、全ての文字が明瞭に読めなければならない。

UKAS 認証マークの色は黒、レターヘッドの印刷と同じ色、もしくは下記の指定色を使用しなければならない。

UKAS マークの色は：金：PMS 872、ブルー：PMS Reflex Blue、赤：PMS Warm Red 又は緑：PMS 347



ISO9001, 14001, 情報セキュリティ共通

UKAS 認証マークは、上述 3.2 項に加えて下記（製品が認証されていると誤解されるもの）への使用制限がある。

衣服類、コップ、皿、その他の食器・台所用具類、ペン、鉛筆、時計、自動車、自動車用ステッカー、旗、看板、窓用ステッカー等

尚、TickIT マークは DISK TickIT Office に規定された色の中のいずれかひとつまたは複数の色を使用しなければならない。円及び円内の文字は黒、Tick 部は赤 (Pantone 032)、Tick の影と IT の文字は淡いグレー (Pantone 8 又は 30%黒) とする。



3.3.3.2 UKAS 認証マーク (旧タイプ)

2014 年 9 月 1 日以降、如何なる企業も本マークを使用する事は出来ない。



3.3.4 JIPDEC 認証マーク

2011 年 10 月 1 日より、新タイプが導入された。2011 年 10 月 1 日以降に認証取得した企業が JIPDEC 認証マークを使用する場合には、新マーク（下記の 3.3.4.1 項）を使用すること。



3.3.4.1 JIPDEC Certification Mark (new type)

JIPDEC certification mark can be reproduced in any size. Even the size being reduced, all letters within the mark shall be clearly legible.

The colour of JIPDEC accreditation mark is as follows. In the case of process colour : (C100%+M70%), in the case of special print colour : (DIC220) single colour. For homepage or electronic information, as a principle, it will be as follows. In the case of using WEB colour slider: (003399), RGB colour: (R=000, G=051, B=153).

3.3.4.2 JIPDEC Certification Mark (old type)

After April 1st, 2016, No Customers can use this Certification Mark.

3.3.5 Combined Marks

Several combined marks with RvA, UKAS, JAB, JIPDEC etc. can be reproduced to satisfy any restrictions as per above 3.3.1 - 3.3.4 concerned. The certification mark shall not be larger than the certificate holders own logo on the same letterhead etc. Even the size being reduced, all letters within the mark shall be clearly legible. The certification mark may be used in black or in the exact colours to satisfy 3.3.1 - 3.3.4.

3.4 All certification mark must not be used, under any circumstances, on or closely associated with products in such a way as to imply that the product itself is certified, on such as any packaging of products (including labels and boxes) or trade samples (including promotional items), certificate of product conformity etc.

3.5 Where there is evidence of misuse of either certification mark or the certificate by the certificate holder, action taken could be one or more of the following:

- Prohibition of using DNV certification mark
- Informing the certificate holder of the required corrective action to be taken on its part.
- Suspension or withdrawal of the certificate.
- Publication of the transgression.
- Legal action.

The type of action taken will be influenced by the nature of the misuse, its subsequent consequences and whether or not

3.3.4.1 JIPDEC 認証マーク (新タイプ)

JIPDEC 認証マークのサイズはどのようなサイズに複製しても良い。縮小する場合、マーク内の文字は明瞭に表示できなければならない。

JIPDEC 認定マークの色は、プロセスカラーの場合: (C100%+M70%)、特殊印刷色の場合: (DIC220) 1色とする。ホームページや電子情報に表示する場合の色指定は、原則として、WEB カラー-sliderで指定の場合 (003399)、RGB カラーで指定の場合 (R=000, G=051, B=153) とする。



3.3.4.2 JIPDEC 認証マーク (旧タイプ)

2016年4月1日以降、如何なる企業も本マークを使用する事は出来ない。



3.3.5 組合せ認証マーク

RvA, UKAS, JAB, JIPDEC 等の各種組合せ認証マークを複製する際のサイズ制限等については、上記の関連する 3.3.1~3.3.4 を全て満足する範囲とする。認証マークは同じレターヘッド等に使われているその企業のロゴより大きくしてはならない。縮小する場合、マーク内の文字は明瞭に表示できなければならない。認証マークの色は黒、もしくは 3.3.1~3.3.4 に表示されている指定色を満足する範囲で使用しなければならない。

3.4 全ての認証マークはいかなる場合においても製品に付けてはならない。また、製品の包装 (ラベルや各種パッケージ類を含む) 又は商品見本 (販促品含む)、製品の検査成績書等を含めて、製品自身に対して認証が与えられたと思われるようないかなる方法でも製品に関連づけて使用してはならない。

3.5 認証を取得した企業が認証マーク又は認証証明書の使用条件に違反したことが明らかになった場合は、以下のいずれかの処置が取られる:

- DNV 認証マークの使用禁止
- 違反事実に対する必要な是正勧告
- 認証証明書の停止又は取り下げ
- 違反事実の公表
- 法的処置

どのような処置がとられるかは、違反事実の内容、それによって及ぼされる影響、及びその違反が不注意に

the misuse was inadvertent or deliberate.

3.6 Notwithstanding 3.5 above the certificate holder shall immediately discontinue any use of the certification mark which is considered unacceptable by DNV Region Japan. In any such event the decision of the General Manager of DNV Business Assurance Japan KK shall be final.

3.7 In the event that a certificate ceases to be valid for whatever reason, the certificate holder shall immediately discontinue all use and distribution of any letter heads, promotional literature etc., bearing the DNV certification mark.

4. USE OF THE DNV CERTIFICATION MARK

4.1 Organisations certificated by DNV under its management system certification scheme are entitled to use the DNV certification mark on its own instead of above certification mark combinations with the mark of accreditation body.

4.1.1 Holders of a management system certificate are entitled to use DNV certification mark on its own on promotional materials including flags and vehicles in addition to the cases described in above 3.2.

4.1.2.1 New type DNV certification mark has been introduced from October 1st, 2011.
The certificate holder who is certified after October 1st, 2011 shall use new one (as per 4.1.2.2) if they use the certification mark.

4.1.2.2 DNV certification mark on its own may be reproduced in any size, however it must always be reproduced in its entirety, including the surrounding outline (for the combined mark with accreditation mark).
DNV certification mark on its own may be reproduced in either black, one colour with company's predominant ink or the exact colours indicated hereafter.

Background to anchor and balance, Standard, Single line :
Blue PMS 286 (DIC 222)
Background to DNV, Double Line :
Green PMS 370 (DIC 375)

4.1.2.3 After October 1st, 2014, No Customers can use this Certification Mark.

よるものかによって決められる。

3.6 上記 3.5 の規定にかかわらず、認証取得企業は DNV が不適当と判断した認証マークの使用を直ちに中止しなければならない。この場合の最終決定は、DNV ビジネス・アシュアランス・ジャパン株式会社 ゼネラルマネージャーが下すものとする。

3.7 どのような理由であっても、認証証明書の効力が失効した場合は、認証取得企業は認証マークの入った全てのものの使用及び配布を直ちに中止しなければならない。

4. DNV 認証マーク使用条件

4.1 DNV マネジメントシステム認証スキームに基づき認証を受けた企業は、上述の認定機関のマークを含む認証マークの代わりに、DNV 認証マークを使用することも出来る。

4.1.1 マネジメントシステム認証証明書を取得した企業は、DNV 認証マークの場合には、前述 3.2 項に加えて、社旗や社有車等のその他の宣伝媒体に使用することが出来る。

4.1.2.1 2011 年 10 月 1 日より、新タイプが導入された。2011 年 10 月 1 日以降に認証取得した企業が DNV 認証マークを使用する場合には、新マーク（下記の 4.1.2.2 項）を使用すること


4.1.2.2 DNV 認証マークはどのようなサイズに複製しても良いが、（認定機関マークとの統合の場合）必ず外枠の線を含めてその全体を複製しなければならない。
DNV 認証マークの色は、黒、企業の主色（単色）もしくは下記の指定色を使用しなければならない。

錨と天秤のバック、規格名、一重ラインは青：
PMS 286 (DIC 222)
DNV のバック、二重ラインは緑：
PMS 370 (DIC 375)



ISO9001 用 ISO14001 用
(他規格も同様)

4.1.2.3 2014 年 10 月 1 日以降、如何なる企業も本マークを使用する事は出来ない。



ISO9001 用 ISO14001 用
(他規格も同様)

4.1.3 For other conditions of use of DNV certification mark on its own, refer to above paragraph 2, 3.1-3.3, 3.4-3.7 as general restrictions.

4.1.3 その他、DNV 認証マーク使用に関しては、前述 2、3.1～3.3 項、3.4～3.7 項の各種一般的な制限条件も参照のこと。